
Model IP2000

Injection & Sampling System Fixed Length with NPT Pipe Plug



Model IP2000 Injection & Sampling System is a fixed-length, 3/4" NPT pipe plug-mounted unit commonly used in field and plant applications. Process shutdown or process isolation is required for installation and inspection. The unit assembly consists of an insertion rod, a welded pipe plug, and an injection/sampling tip. The injection tip, which is threaded, welded, or machined to the end of the rod, can be either a quill, open, cap & core, or nozzle assembly type. Insertion length (I.L.) is calculated to the end of the rod and is based on a customer specified length. For standard injection systems, the maximum insertion length is given in the chart below. The standard pipe plug for the IP2000 is the 3/4" NPT pipe plug, although other options are available.

Specifications:

Body - 316 Stainless Steel **Temperature Rating** - 850°F / 454°C **Pressure Rating** - 3000 PSI / 204 Bar **Mounting** - 3/4" NPT Pipe Plug

| Std. Length | I.L. (max) | | |
|-------------|------------|--|--|
| 6" | 2.8" | | |
| 8" | 4.8" | | |
| 12" | 8.8" | | |
| 18" | 14.8" | | |
| 24" | 20.8" | | |



Houston Office: 6327 Teal Mist Lane, Fulshear, TX 77441 Phone: (832) 451-6825

IP2000 Ordering Information

| Model | | | | | | | | | | | |
|-------|---------|--|--------------|--------------------------|---|--------------------------------------|-----------------------------------|---------------------|--|--|--|
| IP2 | Injecti | ction & Sampling System Fixed Length with NPT Connection | | | | | | | | | |
| | Pipe | Plug Si | Size | | | | | | | | |
| | 2 | 3/4" N | PT Pipe Plug | | | | | | | | |
| | 3 | 1" NP | Pipe Plug | | | | | | | | |
| | | Insert | ion Ro | on Rod Material | | | | | | | |
| | | 2 | 316 | | | | | | | | |
| | | 4 | C276 | | | | | | | | |
| | | | Moun | Mounting Material (Plug) | | | | | | | |
| | | | 2 | 316 | 316 | | | | | | |
| | | | 4 | C276 | C276 | | | | | | |
| | | | | Inject | tion Ti | p Option | ıs | | | | |
| | | | | 01 | | (Straight) |) | | | | |
| | | | | 02 | 1 | (Raised) | | | | | |
| | | | | 03 04 | _ · | | | | | | |
| | | | | 05 | 1 | • | , | | | | |
| | | | | 06 | Head with Cap & Core (9/16") 1/4" NPT (Male) with Nozzle* | | | | | | |
| | | | | | Tube | Size | | | | | |
| | | | | | 01 | 3/8" | | | | | |
| | | | | | 02 | 1/2" | | | | | |
| | | | | | 03 | 5/8" | | | | | |
| | | | | | Length | | na oution loweth | | | | |
| | | | | | 06 2.8 inches max. 08 4.8 inches max. | | | _ | | | |
| | | | | | | 12 | 9 | | _ | | |
| | | | | | | 18 | 14.8 inches max. insertion length | | | | |
| | | | | | | 24 20.8 inches max. insertion length | | | | | |
| | | | | | | | Dry End Mount Options | | | | |
| | | | | | | | | Blanked o | ff | | |
| | | | | | | | 02 | 1.2" NPT | | | |
| | | | | | | | 03 | 3/4" NPT | | | |
| | | | | | | | 04 14 | 1" NPT 1/2" FNPT | - | | |
| | | | | | | | Insertion Length | | | | |
| | | | | | | | | -LLLL | Length in inches, stated in 2 decimal | | |
| | | | | | | | | | place format. Round calculated length down to the nearest 1/8". (Ex: 5 1/8" = 0512) | | |
| IP2 | 2 | 2 | 2 | 02 | 03 | 12 | 02 | -0512 | Example of Probe Ordering # | | |

For alloys, sizes, or other special requirements not listed, contact our sales department.

^{*} Nozzles must be ordered separately.